


Hose Valves



Angle Valves



A55/A56

Female x Male

- Used as fire hose outlet connections
- Female NPT inlet x Male hose thread outlet, 300 PSI, cast brass*, UL listed/FM approved

Model No.	Size	A	B Open	C	D	Swing Radius
A55	1 1/2" x 1 1/2"	4"	7 3/4"	2 1/4"	2"	2 1/2"
A56	2 1/2" x 2 1/2"	5 1/4"	11"	3 1/4"	2 3/4"	3 1/2"


Female x Female

- Used with hose rack assemblies
- Female NPT inlet and outlet, 300 PSI, cast brass*, UL listed/FM approved

Model No.	Size	A	B Open	C	D	Swing Radius
A55	1 1/2" x 1 1/2"	4"	7 3/4"	2 1/4"	2"	2 1/2"
A56	2 1/2" x 2 1/2"	5 1/4"	11"	3 1/4"	2 3/4"	3 1/2"


*Optional brass finishes add suffix to model no.

-B Polished; -C Rough Chrome Plated; -D Polished Chrome Plated



A55/A56

Pressure Restricting Angle Valves



R55/R56

Female x Male

- Used as fire hose outlet connections
- Field-adjustable restricting mechanism reduces water pressure under flowing conditions (175 PSI max. inlet). When full flow is required, restriction can be over-ridden by trained personnel
- Female NPT inlet x Male hose thread outlet, 175 PSI, cast brass*, UL listed

Model No.	Size	A	B Open	C	D	Swing Radius
R55	1 1/2" x 1 1/2"	4"	8"	2 1/4"	2"	2 1/2"
R56	2 1/2" x 2 1/2"	5 1/4"	11 1/2"	3 1/4"	2 3/4"	3 1/2"


Female x Female

- Used with hose rack assemblies
- Field-adjustable restricting mechanism reduces water pressure under flowing conditions (175 PSI max. inlet). When full flow is required, restriction can be over-ridden by trained personnel
- Female NPT inlet and outlet, 175 PSI, cast brass*, UL listed

Model No.	Size	A	B Open	C	D	Swing Radius
R55	1 1/2" x 1 1/2"	4"	8"	2 1/2"	2"	2 1/2"
R56	2 1/2" x 2 1/2"	5 1/2"	11 1/2"	3 1/2"	2 1/2"	3 1/2"

*Optional brass finishes add suffix to model no.

-B Polished; -C Rough Chrome Plated; -D Polished Chrome Plated



R55/R56